


16-ch Relay and 16-ch Isolated Digital Input PCI Card



Features

- 16 opto-isolated digital input channels
- 16 relay actuator output channels
- LED indicators to show activated relays
- Jumper selectable dry contact/wet contact input signals
- BoardID switch



Introduction

The PCI-1762 provides 16 opto-isolated digital inputs with isolation protection of 2,500 V_{DC} for collecting digital inputs in noisy environments, 16 relay actuators that can be used as a on/off control devices or small power switches.

For easy monitoring, each relay is equipped with one red LED to show its on/off status. Each isolated input supports both dry contact and wet contact so that it can easily interface with other devices when no voltage is present in the external circuit.

Specifications

Isolated Digital Input

Channels
16

• Input Voltage Logic 0: 3.0 V max.

Logic 1: 10 V min. (50 V max.)

Interrupt Capable Ch. 2 (IDIO,IDI8)
Isolation Protection 2,500 V_{DC}
Opto-Isolator Response 100 µs
Input Resistance 5.7 k Ohm 1 W

Relay Output

Channels

Relay Type Form A or Form B (Jumper selectable)
Contact Rating 0.5 A @ 250 V_{AC}, 0.5 A @ 30 V_{DC}

Max. Switching Power
Max. Switching Voltage
Operate Time
Release Time
Resistance
125 VA, 15 W
Typical: 250 V_{AC}, 220 V_{DC}
Typical: 3 ms, Max.: 5 ms
Typical: 2 ms, Max.: 4 ms
Contact: 50 m Ohm max.

■ Life Expectancy 2 x 10⁵ cycles min. @ 0.5A/ 250V_{AC}

General

Ordering Information

• PCI-1762 16-ch Relay and 16-ch Isolated Digital Input PCI Card

5 ~ 95 % RH, non-condensing

Accessories

Storage Humidity

PCL-10162-1E DB62 Cable, 1 m
PCL-10162-3E DB62 Cable, 3 m

ADAM-3962 DB62 DIN-rail Wiring Board

ADVANTECH

Data Acquisition Boards