

Communication Port

TR-50U2 Features and Specs

Communication with PC
USB


Communication with Loggers
Optical Communication

The TR-50U2 is a communication port for making settings in and downloading data to PC from our loggers.

Simple USB Connection to PC

Communication can be carried out by simply connecting to a PC and placing the logger face down on the TR-50U2. Compatible with some discontinued products.

Place logger on TR-50U2



| | TR-50U2 |
|--------------------------|---|
| Compatible Devices | TR-5i Series: TR-51i / 52i / TR-55i-TC / 55i-Pt / 55i-V / 55i-mA / 55i-P TR-5S Series: TR-51S / 52S TR-5 Series: TR-51A / 52 |
| Communication Interfaces | Between TR-50U2 - Data Logger(s): Optical Communication Between TR-50U2 - PC: USB Communication |
| Communication Time | TR-5i/5S Series: About 20 sec. TR-5 Series: About 160 sec. |
| Power | USB bus power |
| Dimensions | H 80 mm x W 56 mm x D 16.5 mm |
| Weight | Approx. 25 g |
| Operating Environment | Temperature: -10 to 60 °C Humidity: 90%RH or less (no condensation) |
| Accessories | USB Mini-B Cable US-15C, Software CD-ROM, User's Manual Set (Warranty Included) |

The specifications listed above are subject to change without notice.