



Universal Process Indicator

N1500



DESIGNED FOR
HIGH-RESOLUTION
VIEWING



- High responsiveness to process variable
- Allows visual acuity at a distance
- Timer function for safety alarms
- 30-point linearization for non-standard sensors



N1500 universal process indicator works at fast sampling rate, which ensures high-performance indication and reaction to fast processes dynamics. With 6 digits for high-resolution variables and the 17mm height display, **N1500** provides clear view, making it easier for operators to read and diagnose from a distance.

Its timer function performs wide action capabilities through

alarms for safety interlock logic. Furthermore, **N1500** is fully compatible with custom signals through its linearized input for up to 30 points.

Both electronic robustness and anti-flame material enclosure comply with the main world-class approvals for industry devices.

NOVUS
We Measure, We Control, We Record



TIMER ALARM

Safety interlock logic



DETACHABLE FRONT PANEL

Easy commissioning



FAST SAMPLING RATE

Ideal for dynamic
processes



PROTECTION AND SAFETY

Anti-flame material
UL94 V-2



CUSTOM LINEARIZATION

30-point for
non-standard sensors

Display	7-segment LED, 6-digit with 17 mm height
Input Type	Thermocouples J, K, T, N, R, S, B, E, Pt100, 0-20 mA, 4-20 mA, 0-50 mV, 0-5 Vdc, 0-10 Vdc, 4-20 mA no linear, 0-20 mA custom linear, 4-20 mA custom linear, 0-20 mA custom no linear, 4-20 mA custom no linear
Accuracy	Thermocouples J, K, T: 0.25% of span $\pm 1^\circ\text{C}$ Thermocouples N, R, S, B: 0.25% of span $\pm 3^\circ\text{C}$ Pt100, 0-20 mA, 4-20 mA, 0-5 Vdc, 0-10 Vdc: 0.2% of the span
Sampling Rate	5 samples per second for Pt100 and Thermocouples 15 samples per second for 0-50 mV, 4-20 mA, 0-5 V and 0-10 V
Display Resolution	Temperature: 1 / 0.1 Other measures: 1 / 0.1 / 0.01 / 0.001 / 0.0001
Custom Linearization	30 points for non-standard sensors
Digital Input	Operates as a key for Hold, Peak Hold and maximum/minimum reset
Analog Output	0-20 mA or 4-20 mA (optional) - electrically isolated
Alarms	Up to 4 alarms
Alarm Types	Minimum, maximum, minimum differential, maximum differential, differential out of range, differential within range, and open sensor
Timer Function	Alarms with delay, pulse or oscillator timing

Auxiliary Power Supply	24 Vcc
Optional	2 relays, analog output (4-20 mA or 0-20 mA), RS485
Communication	RS485 Modbus RTU optional
Math Function	Square Root
Safety	Password protected configuration
Configuration Interface	Via RS485
Power Supply	100-240 Vac / dc or 12-24 Vdc
Maximum Consumption	7.5 VA
Dimensions	96 x 48 x 92 mm (1/8 DIN)
Front Panel	IP65 Polycarbonate (PC) UL94 V-2
Enclosure	IP20 ABS + PC UL94 V-0
Operating Conditions	5 to 50 °C, and 0 to 80% RH up to 30 °C
Approvals	CE, UL and cUL

20200708 - FL - N1500 - EN