



RS-485 Modbus RTU Interface to 16 Isolated Inputs / 16 Reed Relay Outputs

Part: 410M | **Model:** Seal/O-410M

The Seal/O-410M is an RS-485 Modbus RTU interface to 16 optically isolated inputs and 16 Reed relay outputs. Inputs can range from 5-30VDC, while the Reed relays provide long-life switch closures well suited to low current devices. Inputs and outputs are grouped into four-bit segments that each share a common for easy wiring via removable 3.5mm terminal blocks. The Seal/O-410M is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-410M using industry-standard Modbus RTU protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems.

Expand your I/O network with Seal/O N-series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

Get a jump start on your digital I/O development with The Digital I/O Handbook that will provide helpful information that you will use again and again. Check out Chapter 1 for an overview of logic principles.

Delivering Design & Manufacturing Excellence Since 1986
WORLD CLASS. AMERICAN MADE.

SEALEVEL®

Features & Specifications

RS-485 Modbus RTU Interface to 16 Isolated Inputs / 16 Reed Relay Outputs

Part: 410M | **Model:** Seal/O-410M

Features

- RS-485 Modbus RTU interface
- 16 SPST Form A Reed relays
- 16 optically isolated inputs
- Removable screw terminals simplify field wiring
- Input power via terminal block or modular connector
- DIN rail or table mount
- Sealevel SeaMAX software supports Microsoft Windows and Linux operating systems

Specifications

Family	Seal/O
Contact Bounce Time	0.5ms max.
Contact Current	500mA max.
Contact Operate Time	0.5ms max.
Contact Release Time	0.2ms max.
Contact Voltage	60VDC max.
Digital I/O	Isolated Inputs, Reed Relay Output
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)
Extended Temperature	Call for Options
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Input Isolation	300V
Input Range	5-30 VDC
Host Interface(s)	RS-485
Number of Inputs/Outputs	16 Inputs / 16 Outputs
Operating Temperature	0°C to 70°C (32°F to 158°F)
# of Ports	16/16
Power Requirement	9-30 VDC @ 1.4W
RoHS Compliant	Yes
Storage Temperature	-50°C to 105°C (-58°F to 221°F)