



\* Specifications, color and design of the products are subject to change without notice.

### Features

# Opto-coupler isolated input (supporting current sink output) and opto-coupler isolated open-collector output (current sink type)

This product has the opto-coupler isolated input 8 channels (supporting current sink output) and opto-coupler isolated open collector output (current sink type) 8 channels whose response speed is 300µsec. Supporting driver voltages of 12 - 24 VDC for I/O. (12 - 24VDC external circuit power supply is required separately.)

# Compatible to USB1.1/USB2.0 and not necessary to power this product externally as the bus power is used.

Compatible to USB1.1/USB2.0 and capable to achieve high speed transfer at HighSpeed (480 Mbps).

#### Opto-coupler bus isolation

As the USB (PC) is isolated from the input and output interfaces by optocouplers, this product has excellent noise performance.

# Output circuits include zener diodes for surge voltage protection and poly-switches for overcurrent protection.

Zener diodes are connected to the output circuits to protect against surge voltages. Similarly, polyswitches are fitted to each group of 8channels outputs for over-current protection.

The output rating is max. 35VDC, 100mA per channel.

#### Windows compatible driver libraries.

Using the driver library API-USBP(WDM) makes it possible to create applications of Windows. In addition, a diagnostic program by which the operations of hardware can be checked is provided.

# Easy-to-wire terminal connector adopted

Adoption of terminal connector (with screws) enables to achieve easy wiring.

#### LabVIEW is supported by a plug-in of dedicated library VI-DAQ.

Using the dedicated library VI-DAQ makes it possible to make a LabVIEW application.

This product is a USB 2.0 compliant terminal that extends the digital signal I/O functions of a PC. This product is a 12 - 24VDC opto-coupler isolated type that does not require external power with input 8 channels and open-collector output 8 channels. In addition, output transistor protection circuit (surge voltage protection and overcurrent protection) are provided. Windows/Linux driver is supported with this product.

Possible to be used as a data recording device for LabVIEW, with dedicated libraries.

- \* The contents in this document are subject to change without notice.
- \* Visit the CONTEC website to check the latest details in the document.
- \* The information in the data sheets is as of November, 2022.

Creations

	Specifications					
		ltem	Specifications			
Inpu	ut section					
	Number of input signal points		8 points (1 common)			
	Input format		Opto-isolated input (Compatible with current sink output) (Negative logic *1)			
	Input resistance		4.7 kΩ			
	Input ON current		2.0mA or more			
	Input OFF current		0.16mA or less			
	Respons	e time	300µsec within *2			
Out	put sectio	'n				
	Number of output signal points		8 points (1 common)			
	Output format		Opto-isolated open collector output (current sink type) (Negative logic*1)			
	Output	Output voltage	35VDC (Max.)			
	rating	Output current	100mA (per point) (Max)			
	Residual	voltage with	0.5V or less (Output current≤50mA),			
	output o	n -	1.0V or less (Output current≤100mA)			
	Surge pr	otector	Zener diode RD47FM(NEC) or equivalent			
	Response time		300µsec within *2			
USE	3					
	Bus specification		USB Specification 2.0/1.1 standard			
	USB transfer rate		12Mbps (Full-speed), 480Mbps (High-speed) *3			
	Power su	ıpply	Bus power			
Con	nmon					
	Connect	or	14 pin (screw-terminal) plug header			
	Number of terminals used at the same time		127 terminals (Max) *4			
	Dielectric	strength	1000Vrms			
	External circuit power supply *5		12 - 24VDC (±10%)			
	Current consumption (Max)		5VDC 250mA			
	Operatin	g conditions	0 - 50°C, 10 - 90%RH (No condensation)			
	Allowable distance of signal extension		Approx. 50m (depending on wiring environment)			
1	Physical dimensions (mm)		64(W) x 62(D) x 24(H) (exclusive of protrusions)			
1	Weight		70g (Not including the USB cable, attachment)			
1	Attached cable		USB cable 1.8m			
1	Compatible wires		AWG28-16			
	Standard		FCC Class A, VCCI Class A, CE Marking (EMC Directive Class A, RoHS Directive), UKCA, KC			

\*1 Data "0" and "1" correspond to the High and Low levels, respectively.

\*2 The opto-coupler's response time comes.

- \*3 This depends on the host PC environment used (OS and USB host controller).
- \*4 As a USB hub is also counted as one device, you cannot just connect 127 USB terminals.
- \*5 External circuit power supply is required separately.

# © CONTEC



# **Included Items**

Product [DIO-0808LY-USB] ...1 Please read the following ... 1 Interface connector plugs ...2 USB Cable (1.8m) ... 1 USB Cable Attachment ... 1

Optional Products						
ProductName	Model type	Description				
Connector	CN6-Y14	14pin Screw Terminal Connector Set (6 pieces)				
Bracket	BRK-USB-Y	Bracket for USB I/O Terminal products				

\* Information about the option products, see the Contec's website.



#### List of Status LED Functions

Name	Function	Indicator color	LED indicator
	USB communication		ON : Communication established
LINIX Status	status		OFF : Communication unestablished
LINK SIdius	PC connection status	GREEN	ON : PC communication established
			OFF : PC communication unestablished

# Support Software

#### Driver Library API-USBP(WDM) (Available for downloading (free of charge) from the CONTEC web site.)

It is the library software, and which supplies command of hardware produced by our company in the form of standard Win32 API function(DLL). Using programming languages supporting Win32API functions, such as Visual Basic and Visual C++ etc., you can develop high-speed application software with feature of hardware produced by our company.

In addition, you can verify the operation of hardware using Diagnostic programs.

### Data acquisition VI library for LabVIEW VI-DAQ

# (Available for downloading (free of charge) from the CONTEC web site.)

This is a VI library to use in National Instruments LabVIEW.

VI-DAQ is created with a function form similar to that of LabVIEW's Data Acquisition VI, allowing you to use various devices without complicated settings.

# Using the On-terminal Connectors



# Using the On-terminal Connectors

## Connecting a terminal to a Connector

To connect an external device to this terminal, plug the cable from the device into the interface connector (CN1, CN2) shown below.



## **Connector Pin Assignment**

CN1	CN2
0 14 O-PC   13 O-PC   13 O-PC   13 O-PC   14 O-PC   13 O-PC   14 O-PC   13 O-PC   14 O-00   10 O-01   9 O-04   6 O-05   5 O-06   4 O-07   3 N.C.   1 O-NC   1 O-NC	N.C 1 N.C 2 N.C 3 I-07 4 I-06 5 I-05 6 I-04 7 I-03 8 I-02 9 I-01 10 I-00 11 N.C 12 I-PC 14

I-00 - I-07	8 input signal pins.	
	Connect output signals from the external device to these pins.	
O-00 - O-07	8 output signal pins.	
	Connect these pins to the input signal pins of the external device.	
I-PC	Connect the positive side of the external power supply.	
	These pins are common to 8 input signal pins.	
O-PC	Connect the positive side of the external power supply.	
	These pins are common to 8 output signal pins.	
O-NC	Connect the negative side of the external power supply.	
	These pins are common to 8 output signal pins.	
N.C.	This pin is left unconnected.	

#### Cable connection

When connecting the product to an external device, you can use the supplied connector plug.

For wiring, strip off approximately 9 - 10mm of the covered part of a wire rod and then insert it to the opening. After the insertion, secure the wire rod with screws. Compatible wires are AWG 28 - 16.

#### A CAUTION

Removing the connector plug by grasping the cable can break the wire.

# © CONTEC



# Input Circuit

Input Circuit



#### Input pin: O-xx

The input circuit of this product is illustrated in the image above.

It is connected to devices such as switch and transistor output devices, which can be powered by an electric current. The ON/OFF state of a device that can be powered by an electric current is entered as a digital value.

The input channels are to be connected with current sinking output signals. Driving these opto-isolated circuits require an additional power supply isolated from the PC system. When a 12VDC external power is used, each input channel will consume about 2.6mA current; when a 24VDC external power supply is selected, each input channel will consume about 5.1mA current.

#### Connecting a Switch



When the switch is ON, the corresponding bit contains 1. When the switch is OFF, by contrast, the bit contains 0. Output Circuit

## **Output Circuit**



#### \* Output pin: O-xx

The output circuit of this product is illustrated the image above. The signal output section is an opto- isolated, open-collector output (current sink type). Driving the output section requires an external power supply.

The rated output current per channel is 100 mA at maximum. The output section can also be connected to a TTL level input as it uses a low-saturated transistor for output. The residual voltage (low-level voltage) between the collector and emitter with the output on is 0.5 V or less at an output current within 50 mA or at most 1.0 V at an output current within 100 mA.

A zener diode is connected to the output transistor for protection from surge voltages. A PolySwitch-based over-current protector is provided for every eight output transistors. When the over-current protector works, the output section of the product is temporarily disabled. If this is the case, turn of the power to the PC and the external power supply and wait for a few minutes, then turn them on back.

### 

When the PC is turned on, all output are reset to OFF.

### Example of Connection to LED



When "1" is output to a relevant bit, the corresponding LED comes on. When "0" is output to the bit, in contrast, the LED goes out.

DIO-0808LY-USB

4

# Example of Connection to TTL Level Input



# Connecting the Sink Type Output and Sink Output Support Input

The following example shows a connection between a sink type output (output side) and a sink output support input (input side). Use this sample connection as a reference when connecting more than one of this product together.



DIO-0808LY-USB