

DATENBLATT

PI-D SERIAL-PCI/LP

HABEN SIE FRAGEN ODER WÜNSCHEN SIE EIN INDIVIDUELLES ANGEBOT?

Unser Team berät Sie gerne persönlich.

TELEFON + 49 (0) 81 41/36 97-0

TELEFAX + 49 (0) 81 41/36 97-30

E-MAIL info@plug-in.de

WWW.PLUG-IN.DE

ADRESSE

Am Sonnenlicht 5

D-82239 Alling bei München





Lava The Source for Ports

LAVA DSerial-PCI/LP

PCI Bus Low Profile Dual 16550 Serial Board

Features & Benefits

- Adds two 9-pin 16550 UART serial ports to PCI-equipped low profile PCs
- Each port is capable of a maximum data throughput rate up to 115.2 kbps
- Low profile design (2.5"/60 mm high) fits the new low profile PCI chassis
- Both ports share one IRQ — saves valuable resources for other expansion cards
- Easy Plug and Play installation — automatically selects next available IRQ and I/O addresses
- Includes Lava Com Port Redirect Utility for renaming Com ports — allows for backward compatibility with software that supports Com 1-4 only
- Compatible with RS-232 serial peripherals including modems, PDAs, digital cameras, bar-code scanners, and UPSes
- Includes Y-split cable
- Compliant with PCI Specification 2.1
- Lava Lifetime Warranty

Connectors

- Two DB-9 male RS-232

System Requirements

- PCI host slot
- Low profile PCI chassis

Drivers ship with product. For updated software support visit www.lavalink.com.

FC CE

