DATENBLATT

PT-S959W10C-DC6000

HABEN SIE FRAGEN ODER
WÜNSCHEN SIE EIN INDIVIDUELLES ANGEBOT?
Unser Team berät Sie gerne persönlich.

TELEFON + 49 (0) 81 41/36 97-0
TELEFAX + 49 (0) 81 41/36 97-30
E-MAIL info@plug-in.de
WWW.PLUG-IN.DE

ADRESSE
Am Sonnenlicht 5
D-82239 Alling bei München

Erwähnte Firmen- und Produktnamen sind zum Teil eingetragene Warenzeichen der jeweiligen Hersteller.

Touch Panel PC with Intel® Atom™ D2550
2x LAN, CFast Socket, 4x COM

PT-S959W10C

Wide 10.1-inch | Atom D2550 | IP65

Features

- Intel® Atom™ D2550 processor
- Silent fanless design with thinner chassis
- IP65 front panel for water-proof applications
- 10.1" LCD with long-life touch screen and LED backlight for power saving

Packing List

1x Panel PC

1x DVI-analog RGB adapter

2x CFast card removal prevention fittings

1x Cable clamp

Optional Configuration

AC adapter
2.5 HDD
2.5 SSD
CFast card

Ordering Information

PT-S959W10C-DC6000
10.1" panel-mount, Intel® Atom™ D2550, 2GB DDR3, 4x COM

System	CPU	Intel® Atom™ D2550 1.86GHz processor
	BIOS	AMI BIOS
	Chipset	Intel® NM10 Express
	Memory	Installed 2GB DDR3 RAM module, upgradable up to 4GB
	Watchdog timer	Software programmable, 255 level (1-255 seconds), Reset occurs when the time is up
	Hardware monitor	CPU temperature, board temperature, power monitor
	RTC/CMOS	Backup battery life: 7 years or more lithium
		Precision RTC (25°C) : ±3min/Mon (RTC integrated in NM10)
	Power management	Power management setup by BIOS Power On by Ring / Wake On LAN function PC98/PC99 ACPI power management support
Storage	CFast	1x external CFast sockets
	HDD	1x 2.5" SATA drive bay
I/O	Video (external output)	1x DVI-I
	Serial ports	2x RS-232C ports, 1x RS-232C/422/485 port, 1x RS-422/485 port
	USB ports	4x USB ports, USB 2.0 compliant
LCD panel	Panel size/ resolution/ color	Wide 10.1" TFT-LCD, WSGA (1024 × 600), 260,000 colors
Touch panel	Resolution	2048 x 2048 (emulated in 1024 x 600 mode)
	Detection method	Resistive-film analog type
	Connection	Internal USB port
Graphics	Chipset	Intel® GMA 3650 Graphics
	VGA	Up to 1920 x 1200 (16.77M colors)
	DVI	Up to 1920 x 1200 RB (16.77M colors)
Audio	Interface	HD Audio compliant, Line-out, Mic-in
Ethernet	LAN1, 2	Realtek® RTL8111E PCIe GbE LAN, support wake on LAN
Power	Input voltage range	12 - 24VDC
	Consumption	12V 3.2A (max.), 24V 1.6A (max.)
Mechanical	Dimension (mm)	300 x 57 x 195 (excluding protrusions)
	Panel cut (mm)	224 x 128
Environment	Ambient temperature Horizontal installation	0 - 50℃ (0 -45℃ Optimum operating temperature)
	Storage temperature	-10 - 60℃
	Ambient humidity	10 - 90%RH (no-condensation)
	Waterproofing and dust-proofing	IP65 standard (front panel)
	Certification EMC safety	CE, FCC, RoHS directive
Software operating support		Windows 7 (32-bit)

All specifications are subject to change without notice